




## View Range - Display Tags

Products	 View 2	 View 3	 View 4
<b>Typical Applications</b>	Manufacturing: WIP Instructions and Control  Logistics: Cycling containers and Kanban Warehousing/Yard Management Food Supply Chain  Health Care: Equipment Tracking and labeling	Manufacturing: WIP Instructions and Control  Logistics: Cycling containers and Kanban Warehousing/Yard Management Food Supply Chain  Health Care: Equipment Tracking and labeling	Manufacturing: WIP Instructions and Control  Logistics: Cycling containers and Kanban Warehousing/Yard Management Food Supply Chain  Health Care: Equipment Tracking and labeling
Screen	Eledctrophoretic e-paper display  Full Graphic, 120° viewing angle (in sunlight)	Eledctrophoretic e-paper display  Full Graphic, 120° viewing angle (in sunlight)	Eledctrophoretic e-paper display  Full Graphic, 120° viewing angle (in sunlight)
Diagonal Viewable Area (in)	2.0	2.6	4.3
User Memory Active Passive	24 image pages 128 kb user space	24 image pages 128 kb user space	24 image pages 128 kb user space
Battery: Active Passive	Sealed Battery 20,000 image writes or 5 yrs RF	Sealed Battery 20,000 image writes or 5 yrs RF	Sealed Battery 20,000 image writes or 5 yrs RF
Typical Read Range*: Active Passive	100m 6m	100m 6m	100m 6m
Size (mm)	107 x 60 x 19.4	107 x 60 x 19.4	139 x 94.6 x 19.4
Ingress Protection	IP 65	IP 65	IP 65
Operating Temperature (°C)	0 to +50 °C	0 to +50°C	0 to +50°C
Order Codes +	V2	V3	V4

\* Indoor installation typical power settings shown. Optimal enviroments can significantly enhance performance.

+ Order Option Codes are listed on the datasheets.